

**C90-105TG-PRETUNED**

Connector for FLEXWELL® Elliptical Waveguide E105/EP105, CPR90G Flange, Pre-tuned

Tunable connector for FLEXWELL® Elliptical Waveguide E105/EP105

CPR90G flange, Gasket sealed

Pre-tuned in the factory to achieve optimal electrical performance in a designated frequency range within 10.50 to 11.70 GHz

[FEATURES / BENEFITS](#)**Superior Design**

- Fewer tuning screws
- Better performance

**Quick & Easy Installation**

- Flaring tools not required
- Assemble using standard hand tools performance

Assorted Connector Types

- Standard (non-tunable), tunable and pre-tuned versions are available
- Two basic interface series - flange can mate with either a choke or a cover flange

Technical features**STRUCTURE**

Transmission Line Type		Elliptical Waveguide
Cable Type		E105 / EP105
Model Series		E105 / EP105 Series
Connector Frequency Range	GHz	10.5 - 11.7
Connector Type		Pre-tuned
Sealing Method		Gasket
Gas Inlet		NPT 1/8, tube adaptor not included
Connector Interface		CPR90G

MECHANICAL SPECIFICATIONS

Length	mm (in)	132 (5.2)
Outer Diameter	mm (in)	74 (2.9)
Weight	kg (lb)	1.77 (3.9)

[External Document Links](#)[Installation Instruction](#)[Notes](#)

VSWR / Return loss value 1:1.062 / 30.5 dB @ 10.5 – 11.7

GHz with Premium FLEXWELL waveguide



C90-105TG-PRETUNED

Connector for FLEXWELL® Elliptical Waveguide E105/EP105, CPR90G Flange, Pre-tuned

■ VSWR / Return loss value 1:1.15 / 23.1 dB @ 10.5- 11.7 GHz with Standard FLEXWELL waveguide