

**CLAMP-300**

Cable hanger, non-insulated, bolt-on, for 3" coaxial cable

Hanger, non-insulated, bolt-on for coaxial cable

HCA300, made of stainless steel, kit of 10

FEATURES / BENEFITS

Stainless steel hangers for supporting coaxial cable to tower. Recommended spacing 1m (3 feet).

Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot

**Technical features****GENERAL SPECIFICATIONS**

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Bolt-On, non-insulated
Transmission Line Type		HCA300
Cable Type		Air Dielectric

MECHANICAL SPECIFICATIONS

Cable Size		3
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		10
------------------	--	----

External Document Links**Notes**

If using the Bolt-on hanger series in vertical runs, the hoisting grips need to be kept on the tower.