



The set consists of a hot dip galvanized universal clamp and a rubber clamp lining for FLEXWELL<sup>®</sup> Elliptical Waveguide E65

**FEATURES / BENEFITS****Easy waveguide installation**

- The universal clamp with clamp lining is used for proper and secure installation of elliptical waveguides
- A suitable rubber inlet is included

**Technical features****GENERAL SPECIFICATIONS**

|                        |  |                                  |
|------------------------|--|----------------------------------|
| Product Line           |  | Elliptical Waveguide Accessories |
| Product Type           |  | Hanger                           |
| Hanger Type            |  | Basic clamp with clamp lining    |
| Transmission Line Type |  | E65<br>EP65                      |

**MECHANICAL SPECIFICATIONS**

|                                  |  |                                                              |
|----------------------------------|--|--------------------------------------------------------------|
| Number of Cable / Waveguide Runs |  | 1                                                            |
| Material                         |  | Clamp: Hot dip galvanized steel<br>Clamp Lining: EPDM rubber |

**TEMPERATURE SPECIFICATIONS**

|                       |         |                         |
|-----------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185 ) |
| Storage Temperature   | °C (°F) | -50 to 85 (-58 to 185 ) |

**PACKAGING INFORMATION**

|                  |  |    |
|------------------|--|----|
| Package Quantity |  | 10 |
|------------------|--|----|

**External Document Links****Notes**