

FR-N-1SSM-01-70FS

HYBRIFLEX® RRH Optical Fiber Cable, 1 Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 70 ft

PRODUCT DESCRIPTION

RFS' HYBRIFLEX Remote Radio Head (RRH) hybrid feeder cabling solution combines any combination of optical fiber and/or DC power for RRHs in a single lightweight armored or unarmored cable, making it the world's most innovative solution for RRH deployments. Hybrid, Fiber Optic and DC riser trunk and jumper cables are available in a large variety of fiber counts, DC counts and cross sections. Both pre-connectorized and on-site options are available.

FEATURES / BENEFITS

- Ruggedized, bend-insensitive fiber design with outstanding bending characteristics
- Lightweight solution and compact design Decreases tower loading
- Robust cabling Eliminates need for expensive cable trays and ducts
- Installation of tight bundled fiber optic cable pair directly to the RRH Reduces CAPEX and wind load by eliminating need for interconnection
- Outdoor, black jacket Ensures long-lasting cable protection
- 100% Factory tested Online test results available





TECHNICAL FEATURES

STRUCTURE

Cable Type		HYBRIFLEX®
Fire Performance		Flame Retardant
Length	m (ft)	21.3 (70)

MECHANICAL SPECIFICATIONS

Outer Diameter Nominal	mm (in)	5.5 (0.217)
Cable Weight	kg/m (lb/ft)	0.033 (0.022)
Minimum Bending Radius, Single Bend	mm (in)	66 (2.6)
Minimum Bending Radius, Multiple Bends	mm (in)	83 (3.3)
Recommended / Maximum Clamp Spacing	m (ft)	1 / 1.2 (3.25 / 4)

F/O CABLE SPECIFICATIONS

ı			
l	Number of F/O Strands	1	



FR-N-1SSM-01-70FS

HYBRIFLEX® RRH Optical Fiber Cable, 1 Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 70 ft

		G657-A2 Single Mode, Bend Tolerant	
Core/Clad	μm	9/125	
econdary Protection Nominal	μm (in)	900 (0.035)	
/O Standards (Meets or Exceeds)		UL Listed Type OFNR (UL1666), RoHS Compliant	
Optical Loss	dB/Km	0.5 @ 1310 nm 0.5 @ 1550 nm	
FO Break-out Length (Top)	mm (in)	279 (11)	
O Break-out Length (Bottom)	mm (in) 228 (9) Semi-rigid flame-retardant polyolefin, with hot melt adhesive		
Cable Sealing Method			
Fiber Termination End 1		LC Connector	
Fiber Termination End 2		LC Connector with Elongated Clip	
CABLE JACKET			
UV-Protection Individual and External Jacket		Yes	
acket Material		Flame Retardant, Indoor/Outdoor, PVC, Black	
TESTING AND ENVIRONMENTAL			
Storage Temperature	°C (°F)	-40 to 70 (-40 to 158)	
Operation Temperature	°C (°F)	-40 to 65 (-40 to 149) -20 to 65 (-4 to 149)	
Installation Temperature	°C (°F)		
acket Specifications		UL 1666	
<			
TOP	" 1"	BOTTOM	
TOP	"["	BOTTOM	



FR-N-1SSM-01-70FS

HYBRIFLEX® RRH Optical Fiber Cable, 1 Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 70 ft

ADDITIONAL ASSEMBLIES - 1 PAIR SM FIBER

Length, ft	Model Number
10	FR-N-1SM-01-10FS
20	FR-N-1SM-01-20FS
30	FR-N-1SM-01-30FS
40	FR-N-1SM-01-40FS
50	FR-N-1SM-01-50FS
60	FR-N-1SM-01-60FS
79	FR-N-1SM-01-70FS
80	FR-N-1SM-01-80FS
90	FR-N-1SM-01-90FS
100	FR-N-1SM-01-100FS

ADDITIONAL ASSEMBLIES - 2 PAIR SM FIBER

Length, ft	Model Number
10	FR-N-2SM-01-10FS
20	FR-N-2SM-01-20FS
30	FR-N-2SM-01-30FS
40	FR-N-2SM-01-40FS
50	FR-N-2SM-01-50FS
60	FR-N-2SM-01-60FS
70	FR-N-2SM-01-70FS
80	FR-N-2SM-01-80FS
90	FR-N-2SM-01-90FS
100	FR-N-2SM-01-100FS



FR-N-1SSM-01-70FS

HYBRIFLEX® RRH Optical Fiber Cable, 1 Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 70 ft

ADDITIONAL ASSEMBLIES - 1 STRAND SM FIBER

Length, ft	Model Number
10	FR-N-1SSM-01-10FS
15	FR-N-1SSM-01-15FS
20	FR-N-1SSM-01-20FS
30	FR-N-1SSM-01-30FS
40	FR-N-1SSM-01-40FS
50	FR-N-1SSM-01-50FS
60	FR-N-1SSM-01-60FS
70	FR-N-1SSM-01-70FS
80	FR-N-1SSM-01-80FS
90	FR-N-1SSM-01-90FS
100	FR-N-1SSM-01-100FS
120	FR-N-1SSM-01-120FS
130	FR-N-1SSM-01-130FS
150	FR-N-1SSM-01-150FS
160	FR-N-1SSM-01-160FS
170	FR-N-1SSM-01-170FS

ADDITIONAL ASSEMBLIES - 2 STRAND SM FIBER

Length, ft	Model Number
10	FR-N-2SSM-01-10FS
15	FR-N-2SSM-01-15FS
20	FR-N-2SSM-01-20FS
30	FR-N-2SSM-01-30FS
40	FR-N-2SSM-01-40FS
50	FR-N-2SSM-01-50FS
60	FR-N-2SSM-01-60FS
70	FR-N-2SSM-01-70FS
80	FR-N-2SSM-01-80FS
90	FR-N-2SSM-01-90FS
100	FR-N-2SSM-01-100FS



FR-N-1SSM-01-70FS

HYBRIFLEX® RRH Optical Fiber Cable, 1 Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 70 ft

PRE-PACKED HYBRIFLEX KITS FOR EASY INTEGRATION INTO RAYCAP JUNCTION BOXES

RFS Technologies now offers Kitting options for most hybrid risers and jumpers that include both the cable assembly and the Raycap inserts. For reference, kits have a "K" as the third digit in the model number. HB158 does not require an additional gland/insert for proper installation and sealing into the Distribution Boxes.

Kit Model Prefix	Assembly Prefix	Assembly Qty	Raycap Insert Kit	Insert Kit Contents	Raycap Insert Kit Qty
HBK114	HB114	1	RFS Technologies- TRUNK-KIT	(2) 190 0620, Insert, M75, 1H, 40mm	
HBK058	HBF058		RFS Technologies- JUMP-KIT	(1) 190 0621, Insert, M75, 3H, 22mm, Split w/ plugs	4
HBK012	HBF012		RFS Technologies- JUMP-KIT-2	(1) 190 0903, Insert, M75, 2H, 15mm, Split w/ plugs	
FRK-N	FR-N		RFS Technologies- FIBER-KIT	(1) 190 0657, Insert, M75, 6H, 6.1mm, Split w/ plugs	