

## FR-N-2SSM-01-80FS

HYBRIFLEX® RRH Optical Fiber Cable, 2 Single Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 80 ft

#### PRODUCT DESCRIPTION

RFS' HYBRIFLEX Remote Radio Head (RRH) hybrid feeder cabling solution combines any combination of optical fiber and/or DC power for RRHs in a single lightweight armored or unarmored cable, making it the world's most innovative solution for RRH deployments. Hybrid, Fiber Optic and DC riser trunk and jumper cables are available in a large variety of fiber counts, DC counts and cross sections. Both pre-connectorized and on-site options are available.

## **FEATURES / BENEFITS**

- Ruggedized, bend-insensitive fiber design with outstanding bending characteristics
- Lightweight solution and compact design Decreases tower loading
- Robust cabling Eliminates need for expensive cable trays and ducts
- Installation of tight bundled fiber optic cable pair directly to the RRH Reduces CAPEX and wind load by eliminating need for interconnection
- Outdoor, black jacket Ensures long-lasting cable protection
- 100% Factory tested Online test results available



HYBRIFI FX®

1 / 1.2 (3.25 / 4)

## **TECHNICAL FEATURES**

STRUCTURE
Cable Type

cabic Type		TITDINI EEA®
Fire Performance		Flame Retardant
Length	m (ft)	24.4 (80)
MECHANICAL SPECIFICATIONS		
Outer Diameter Nominal	mm (in)	5.5 (0.217)
Cable Weight	kg/m (lb/ft)	0.033 (0.022)
Minimum Bending Radius, Single Bend	mm (in)	66 (2.6)
Minimum Bending Radius, Multiple Bends	mm (in)	83 (3.3)
Perommended / Maximum Clamp		

## **F/O CABLE SPECIFICATIONS**

**Spacing** 

NI	umbar of F/O Strands	2
INU	ımber of F/O Strands	Z

www.rfstechnologies.com FR-N-2SSM-01-80FS REV: C REV DATE: 22 Feb 2021

m (ft)



# FR-N-2SSM-01-80FS

HYBRIFLEX® RRH Optical Fiber Cable, 2 Single Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 80 ft

F/O Cable Type		G657-A2 Single Mode, Bend Tolerant			
Core/Clad	μm	9/125			
Secondary Protection Nominal	μm (in)	900 (0.035)			
F/O Standards (Meets or Exceeds)		UL Listed Type OFNR (UL1666), RoHS Compliant			
Optical Loss	dB/Km	0.5 @ 1310 nm 0.5 @ 1550 nm			
FO Break-out Length (Top)	mm (in)	279 (11)			
FO Break-out Length (Bottom)	mm (in)	228 (9)			
Cable Sealing Method		Semi-rigid flame-retardant polyolefin, with hot melt adhesive			
Fiber Termination End 1		LC Connector			
Fiber Termination End 2		LC Connector with Elongated Clip			
CABLE JACKET					
UV-Protection Individual and External Jacket		Yes			
Jacket Material		Flame Retardant, Indoor/Outdoor, PVC, Black			
TESTING AND ENVIRONMENTAL					
Storage Temperature	°C (°F)	-40 to 70 (-40 to 158)			
Operation Temperature	°C (°F)	-40 to 65 (-40 to 149)			
Installation Temperature	°C (°F)	-20 to 65 (-4 to 149)			
Jacket Specifications		UL 1666			
11************************************	"L"-	9 <sup>*</sup> [229mm] TYP. 2 PLACES			
TOP		BOTTOM			
TYTERNAL DOCUMENT LINUS		NOTES			
EXTERNAL DOCUMENT LINKS  QuickShip 2.0 Program Information: D	and a l	NOTES Specifically designed for Samsung RRH.			

FR-N-2SSM-01-80FS

On-line Factory Test Results:  $\underline{\text{View}}$ 

REV : C

REV DATE : 22 Feb 2021

www.rfstechnologies.com



## FR-N-2SSM-01-80FS

HYBRIFLEX® RRH Optical Fiber Cable, 2 Single Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 80 ft

#### **ADDITIONAL ASSEMBLIES - 1 PAIR SM FIBER**

Length, ft	Model Number
10	FR-N-1SM-01-10FS
20	FR-N-1SM-01-20FS
30	FR-N-1SM-01-30FS
40	FR-N-1SM-01-40FS
50	FR-N-1SM-01-50FS
60	FR-N-1SM-01-60FS
79	FR-N-1SM-01-70FS
80	FR-N-1SM-01-80FS
90	FR-N-1SM-01-90FS
100	FR-N-1SM-01-100FS

## **ADDITIONAL ASSEMBLIES - 2 PAIR SM FIBER**

Length, ft	Model Number
10	FR-N-2SM-01-10FS
20	FR-N-2SM-01-20FS
30	FR-N-2SM-01-30FS
40	FR-N-2SM-01-40FS
50	FR-N-2SM-01-50FS
60	FR-N-2SM-01-60FS
70	FR-N-2SM-01-70FS
80	FR-N-2SM-01-80FS
90	FR-N-2SM-01-90FS
100	FR-N-2SM-01-100FS

FR-N-2SSM-01-80FS REV : C REV DATE : 22 Feb 2021 www.rfstechnologies.com



## FR-N-2SSM-01-80FS

HYBRIFLEX® RRH Optical Fiber Cable, 2 Single Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 80 ft

#### **ADDITIONAL ASSEMBLIES - 1 STRAND SM FIBER**

Length, ft	Model Number		
10	FR-N-1SSM-01-10FS		
15	FR-N-1SSM-01-15FS		
20	FR-N-1SSM-01-20FS		
30	FR-N-1SSM-01-30FS		
40	FR-N-1SSM-01-40FS		
50	FR-N-1SSM-01-50FS		
60	FR-N-1SSM-01-60FS		
70	FR-N-1SSM-01-70FS		
80	FR-N-1SSM-01-80FS		
90	FR-N-1SSM-01-90FS		
100	FR-N-1SSM-01-100FS		
120	FR-N-1SSM-01-120FS		
130	FR-N-1SSM-01-130FS		
150	FR-N-1SSM-01-150FS		
160	FR-N-1SSM-01-160FS		
170	FR-N-1SSM-01-170FS		

## **ADDITIONAL ASSEMBLIES - 2 STRAND SM FIBER**

Length, ft	Model Number
10	FR-N-2SSM-01-10FS
15	FR-N-2SSM-01-15FS
20	FR-N-2SSM-01-20FS
30	FR-N-2SSM-01-30FS
40	FR-N-2SSM-01-40FS
50	FR-N-2SSM-01-50FS
60	FR-N-2SSM-01-60FS
70	FR-N-2SSM-01-70FS
80	FR-N-2SSM-01-80FS
90	FR-N-2SSM-01-90FS
100	FR-N-2SSM-01-100FS

FR-N-2SSM-01-80FS REV : C REV DATE : 22 Feb 2021 www.rfstechnologies.com



## FR-N-2SSM-01-80FS

HYBRIFLEX® RRH Optical Fiber Cable, 2 Single Strand, Ruggedized Bend-Insensitive Single-Mode Fiber, LC to Elongated LC Clip, 80 ft

## PRE-PACKED HYBRIFLEX KITS FOR EASY INTEGRATION INTO RAYCAP JUNCTION BOXES

RFS Technologies now offers Kitting options for most hybrid risers and jumpers that include both the cable assembly and the Raycap inserts. For reference, kits have a "K" as the third digit in the model number. HB158 does not require an additional gland/insert for proper installation and sealing into the Distribution Boxes.

Kit Model Prefix	Assembly Prefix	Assembly Qty	Raycap Insert Kit	Insert Kit Contents	Raycap Insert Kit Qty
HBK114	HB114	1	RFS Technologies- TRUNK-KIT	(2) 190 0620, Insert, M75, 1H, 40mm	
HBK058	HBF058		RFS Technologies- JUMP-KIT	(1) 190 0621, Insert, M75, 3H, 22mm, Split w/ plugs	4
HBK012	HBF012		RFS Technologies- JUMP-KIT-2	(1) 190 0903, Insert, M75, 2H, 15mm, Split w/ plugs	
FRK-N	FR-N		RFS Technologies- FIBER-KIT	(1) 190 0657, Insert, M75, 6H, 6.1mm, Split w/ plugs	

FR-N-2SSM-01-80FS REV : C REV DATE : 22 Feb 2021 www.rfstechnologies.com