



Plenum-Rated 3/8" Air Dielectric Cable

RFS Technologies' 3/8" air dielectric cable is specifically engineered to meet stringent plenum requirements in both the United States and Canada, ensuring compliance with NEC and NFPA safety standards for use in air-handling spaces. Designed for exceptional RF performance and low loss, this cable is widely used in Distributed Antenna System (DAS) projects for in-building wireless communication, including commercial buildings, airports, hospitals, and other high-density venues. Its flexible construction allows for easy routing in tight plenum spaces, while its robust shielding ensures minimal signal interference. Ideal for applications requiring high signal integrity and regulatory compliance.



FEATURES / BENEFITS

- **High-Frequency Performance up to 6 GHz.** Engineered to support RF signals across a broad frequency range—including up to 6 GHz—this cable meets the demands of today's advanced wireless communication systems, including 5G and future-ready networks.
- **Superior Shielding for Maximum Interference Protection.** The solid outer conductor provides complete 360° RFI/EMI shielding, significantly reducing signal leakage and minimizing system interference in high-density RF environments.
- **Exceptional Intermodulation Performance.** With both solid inner and outer conductors, the cable virtually eliminates passive intermodulation (PIM), ensuring clean signal transmission.
- **Optimized for Plenum-Space Installations.** Engineered to meet plenum-rated safety standards in the U.S. and Canada, this cable is ideal for indoor DAS applications in office buildings, hospitals, airports, and other public venues requiring strict fire safety compliance.

3/8" Plenum-Rated DAS Cable

Technical features

APPLICATIONS

Applications		Wireless Communication	Mobile Radio	In Building	DAS
--------------	--	------------------------	--------------	-------------	-----

STRUCTURE

Size		3/8
Inner Conductor Diameter	mm (in)	3.1 (0.122)
Inner Conductor Material		Copper-Clad Aluminum Wire
Dielectric Diameter	mm (in)	7.5 (0.295)
Dielectric Material		Extruded Polyethylene
Outer Conductor Diameter	mm (in)	9.5 (0.374)
Outer Conductor Material		Corrugated Aluminum
Jacket Diameter	mm (in)	11.2 (0.441)
Jacket Material		PVC, Plenum Rated / Color White
Cable Type		Air-Dielectric, Corrugated



TESTING AND ENVIRONMENTAL

Fire Performance		Flame Retardant, Plenum Rated
Flame Retardant Jacket Specifications		CMP (Communications Multipurpose Plenum)
Regulatory Compliance		NFPA 262 (UL910) / CATVP / CMP / UL444 / Canadian CSA C.22.2/FT6
Installation Temperature	°C(°F)	-20 to 60 (-4 to 140)
Storage Temperature	°C (°F)	-40 to 85 (-40 to 185)
Operation Temperature	°C(°F)	-40 to 85 (-40 to 185)

ELECTRICAL SPECIFICATIONS

Impedance	Ω	50 +/- 2
Maximum Frequency	GHz	6
Velocity	%	86
Capacitance	pF/m (pF/ft)	76 (23.2)
Peak Power Rating	kW	12.8
RF Peak Voltage	Volts	2500
Jacket Spark	Volt RMS	3000
Inner Conductor dc Resistance	Ω /1000 m (Ω /1000 ft)	3.95 (1.20)
Outer Conductor dc Resistance	Ω /1000 m (Ω /1000 ft)	4.80 (1.46)
Return Loss (VSWR) Performance		24 (1.13) @ 698-960 MHz 24 (1.13) @ 1395-1432 MHz 24 (1.13) @ 1700-2155 MHz 20 (1.22) @ 2300-2700 MHz 18 (1.29) @ 3550-4200 MHz 18 (1.29) @ 5150-6000 MHz

MECHANICAL SPECIFICATIONS

Minimum Bending Radius, Single Bend	mm (in)	60 (2.36)
Minimum Bending Radius, Repeated Bends	mm (in)	110 (4.33)
Bending Moment	Nm (lb-ft)	1.9 (1.4)
Tensile Strength	N (lb)	260 (58.5)
Recommended / Maximum Clamp Spacing	m (ft)	0.5 / 0.9 (1.8 / 3)
Crush Strength	kg/mm (lb/in)	1.02 (57.1)

**ICA38-50JPLLW**

3/8" Plenum-Rated Corrugated Aluminum Coaxial Cable, 50 ohm, Up to 6GHz, White Color

ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
200	5.49	1.67	
450	8.34	2.54	
800	11.38	3.47	
900	12.07	3.68	
1500	16.09	4.90	
1800	17.95	5.47	
2000	18.93	5.77	
2200	19.72	6.01	
2500	21.48	6.55	
2700	22.46	6.85	
3000	23.84	7.27	
3400	25.70	7.83	
4000	28.06	8.55	
5000	31.88	9.72	
6000	34.92	10.64	

External Document Links

[LINK TO VEX FILE](#)

Notes