



RSB Clamp Lining for LCF 38 cable and others with $d = 10.5 - 12.5$ mm over jacket (usable in combination with RSB-12).

FEATURES / BENEFITS

The clamp lining has been designed to be used in combination with the RSB-Clip RSB-12. The use of the clamp lining in combination with RSB-Clip prevents LCF38-50 cables against damage e.g. due to cable movement by wind, therefore a deterioration of the electrical properties is avoided.



RSB-38/12

Technical features

GENERAL SPECIFICATIONS

Product Line		Coaxial Cable Accessories Hybrid Cable Accessories
Product Type		Clamp Lining
Transmission Line Type		LCF38
Cable Type		Coaxial Foam Dielectric

MECHANICAL SPECIFICATIONS

Cable Size		3/8
Number of Cable / Waveguide Runs		1
Material		EPDM rubber
Length	mm (in)	34 (1.34)
Height	mm (in)	20 (0.79)
Width	mm (in)	20 (0.79)

ACCESSORIES

Spare Part / Useful Accessories		RSB-Cleat : RSB-12 Cleat : RSB-310 Anchor bar fixation : RSB-315
---------------------------------	--	--

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		1
Weight per piece	kg (lb)	0.005 (0.01)

External Document Links

Notes

Only usable in combination with RSB-12