



The RSB Clip RSB-78 is designed for the installation of CELLFLEX® foam-dielectric cables of 7/8" size. The clip is a universal clamp device and can be used in many mounting configurations. When replacing a cable the clip can be opened without any tools. After replacing the cable the clips are easily closed again. The RSB is the abbreviation of Rostfreier Stahlbügel and means stainless steel hanger. The hanger is resistant against all environmental influences. Due to its mechanical construction cable deformation is impossible and deterioration of the electrical properties is avoided.

**FEATURES / BENEFITS****Technical features****GENERAL SPECIFICATIONS**

|                        |  |                                                                                                 |
|------------------------|--|-------------------------------------------------------------------------------------------------|
| Product Line           |  | Coaxial Cable Accessories<br>Hybrid Cable Accessories                                           |
| Product Type           |  | Hanger                                                                                          |
| Hanger Type            |  | RSB-Clip                                                                                        |
| Transmission Line Type |  | LCF78<br>UCF78<br>RLF78, RLFW78<br>RAY78, RAYB78<br>RLKU78<br>RLKW78<br>RCF78<br>HB078<br>HCA78 |
| Cable Type             |  | Coaxial Foam Dielectric<br>Air Dielectric                                                       |

**MECHANICAL SPECIFICATIONS**

|                                  |         |                 |
|----------------------------------|---------|-----------------|
| Cable Size                       |         | 7/8             |
| Number of Cable / Waveguide Runs |         | 1               |
| Material                         |         | Stainless Steel |
| Drill Hole Size                  | mm (in) | 8 (0.315)       |

**ACCESSORIES**

|                                 |  |                                                  |
|---------------------------------|--|--------------------------------------------------|
| Spare Part / Useful Accessories |  | Cleat : RSB-310<br>Anchor bar fixation : RSB-315 |
|---------------------------------|--|--------------------------------------------------|

**TEMPERATURE SPECIFICATIONS**

|                          |         |                         |
|--------------------------|---------|-------------------------|
| Installation Temperature | °C (°F) | -50 to 85 (-58 to 185 ) |
| Operation Temperature    | °C (°F) | -50 to 85 (-58 to 185 ) |
| Storage Temperature      | °C (°F) | -50 to 85 (-58 to 185 ) |

**PACKAGING INFORMATION**

|                  |  |   |
|------------------|--|---|
| Package Quantity |  | 1 |
|------------------|--|---|



#### External Document Links

[Application Note RSB Clip](#)

[Installation Instruction](#)

#### Notes